



CONNECTED TO INNOVATION



**NEW
RANGE**

PNEUMATIC TOOLS



CLAMPING TOOLS

RATCHET AND IMPACT WRENCHES

Ergonomic Easy to hold		Pressure 6,2 bar		Power of clamping		ID supply hose Ø 10 mm for air inlet R 1/4, Ø 13 mm for air inlet R 3/8, Ø 19 mm for air inlet R 1/2		Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4mm and ARO for quick connection		
		Noise dB(A)	Weight kg	Consumpt. l/min	Drive square	Rotation speed tr/min	Torque Nm	Mecanism	Thread fem. (BSPT)	REFERENCE
New composite air impact wrench - Twin hammer										
	NEW	92,5	1,21	167	3/8"	13500	407	Twin hammer	R 1/4	TIW C380645
		96	2,3	190	1/2"	8000	1085	Twin hammer	R 1/4	TIW C121150
		97,8	3,7	206	3/4"	6000	1763	Twin hammer	R 3/8	TIW C341630
New composite air impact wrench with extended anvil - Twin hammer										
	NEW	96	2,8	190	1/2"	8000	1085	Twin hammer	R 1/4	TIW C121150R
		97,8	4,2	206	3/4"	6000	1763	Twin hammer	R 3/8	TIW C341630R
New composite air impact wrench - Twin hammer - In case										
	NEW	Characteristics identical to wrench TIW C121150 Supplied in case with the following additional accessories: 10-pieces sockets (10, 12, 14, 17, 19, 21, 22, 23, 24, 27mm) 1 x 3" extension 1-piece mini oiler								
	Case	96		190	1/2"	8000	1085	Twin hammer	R 1/4	TIW C121150K
New composite air impact wrench - Twin hammer - In case										
	NEW	Characteristics identical to wrench TIW C341630 Supplied in case with : 5-pieces sockets (24, 27, 30, 32, 33 mm) 1-piece mini-oiler G 1/4								
	Case	97,8		206	3/4"	6000	1763	Twin hammer	R 3/8	TIW C341630K

CLAMPING TOOLS

RATCHET AND IMPACT WRENCHES

Ergonomic Easy to hold	Pressure 6,2 bar	Power of clamping	ID supply hose Ø 10 mm for air inlet R 1/4, Ø 13 mm for air inlet R 3/8, Ø 19 mm for air inlet R 1/2	Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4mm and ARO for quick connection
---------------------------	---------------------	----------------------	---	--

		Noise dB(A)	Weight kg	Consumpt. l/min	Drive square	Rotation speed tr/min	Torque Nm	Mecanism	Thread fem. (BSPT)	REFERENCE
New composite air impact wrench with extended anvil - Twin hammer - In case										
	 	Characteristics identical to driver TIW C121150R Supplied in case with : 10 sockets (10, 12, 14, 17, 19, 21, 22, 23, 24, 27 mm) 1 x 3" extension 1 mini oiler								
		96		190	1/2"	8000	1085	Twin hammer	R 1/4	TIW C121150RK
New composite air impact wrench with extended - Twin hammer - In case										
	 	Characteristics identical to wrench TIW C341630R Supplied in case with : 5-pieces sockets (24, 27, 30, 32, 33 mm) 1-piece mini-oiler G 1/4								
		97,8		190	3/4"	6000	1763	Twin hammer	R 3/8	TIW C341630RK
Compact air impact wrench										
		98	1,55	133	1/2"	10 000	678	Jumbo hammer	R 1/4	TIW K120680
1/2" compact air impact wrench - In case										
	 	Characteristics identical to drivers TIW K120680 Supplied in case with : 6 x 1/2" sockets (13, 17, 19, 21, 22, 24 mm) 1 mini oiler								
		98		133	1/2"	10 000	678	Jumbo hammer	R 1/4	TIW K120680K

CLAMPING TOOLS

RATCHET AND IMPACT WRENCHES

Ergonomic Easy to hold		Pressure 6,2 bar		Power of clamping		ID supply hose Ø 10 mm for air inlet R 1/4, Ø 13 mm for air inlet R 3/8, Ø 19 mm for air inlet R 1/2		Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4mm and ARO for quick connection		
		Noise dB(A)	Weight kg	Consumpt. l/min	Drive square	Rotation speed tr/min	Torque Nm	Mecanism	Thread fem. (BSPT)	REFERENCE
Composite air impact wrench - Twin hammer										
		93	2,15	125	1/2"	8000	949	Twin hammer	R 1/4	TIW C120950
Heavy-duty composite 1/2" impact driver										
		88	2,15	125	1/2"	R 8000 F 2500	R 815 F 108	Twin hammer Limited torque	R 1/4	TIW C12L815
Composite air impact wrench - Twin hammer - In case										
			Characteristics identical to driver TIW C120950. Supplied in case with : 10 x 1/2" sockets (10, 12, 14, 17, 19, 21, 22, 23, 24, 27 mm) 1 x 3" extension 1 mini oiler							
			93		125	1/2"	8000	949	Twin hammer	R 1/4
Limited torque composite air impact wrench - Twin hammer - In case										
			Characteristics identical to drivers TIW C12L815. Supplied in case with : 10 x 1/2" sockets (10, 12, 14, 17, 19, 21, 22, 23, 24, 27 mm) 1 x 3" extension 1 mini oiler							
			88		125	1/2"	R 8000 F 2500	R 815 F 108	Twin hammer Limited torque	R 1/4

CLAMPING TOOLS

RATCHET AND IMPACT WRENCHES

Ergonomic Easy to hold		Pressure 6,2 bar		Power of clamping			ID supply hose Ø 10 mm for air inlet R 1/4, Ø 13 mm for air inlet R 3/8, Ø 19 mm for air inlet R 1/2		Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4mm and ARO for quick connection		
		Noise dB(A)	Weight kg	Consumpt. l/min	Drive square	Rotation speed tr/min	Torque Nm	Mecanism	Thread fem. (BSPT)	REFERENCE	
Composite air ratchet/impact wrench											
	NEW	97	1,8	142	1/2"	7100	244		R 1/4	TIW C120270	
Aluminium air impact wrench											
	NEW	93	2,86	119	1/2"	7000	950	Twin hammer	R 1/4	TIW A120950	
		98	5,6	270	3/4"	5500	1490	Twin hammer	R 3/8	TIW A341490	
Aluminium air impact wrench											
	NEW	103	7,4	255	1"	5000	2440	Twin hammer	R 1/2	TIW A012440	
Aluminium straight impact wrench											
	NEW	106	8,1	225	1"	5000	2712	Twin hammer	R 1/2	TIW A012710	
Air ratchet wrench											
	NEW	91	1,4	113	3/8"	160	68		R 1/4	TRW 38070	
		91	1,32	113	1/2"	160	70		R 1/4	TRW 12070	
		95	1,76	119	1/2"	600	163	Licom hammer	R 1/4	TRW 12160	

SCREW DRIVING

Pressure 6.2 bar	Thread female R 1/4 (BSPT)	ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2	Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4mm and ARO for quick connection
---------------------	-------------------------------	---	--

	Noise	Weight	Consumption	Rotation speed	Chuck	Torque	REFERENCE
1/4" Air screwdriver straight type							
 NEW	102	1,3	142	1800	6,35 mm Hex. 1/4"	5 - 13 Nm	TSD S1800I
Air screwdriver pistol							
 NEW	80	1,35	113	800	6,35 mm Hex. 1/4"	5 - 16 Nm	TSD P0800I
	80	1,2	113	1800	6,35 mm Hex. 1/4"	5 - 16 Nm	TSD P1800I
Torque control straight air screwdriver							
 NEW	82	0,75	113	1000	4mm - 5/32"	0,4 - 2 Nm	TSD S1000E
Torque control screwdriver pistol							
 NEW	76	1,1	113	1700	6,35 mm Hex 1/4"	1 - 1,7 Nm	TSD P1700E



SANDING

Pressure 6,2 bar	Easy to handle	Thread female R 1/4 (BSPT)	ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection				
		Noise dB	Weight kg	Consumption l/min	Rotation speed rpm	Offset mm	Diameter plate	REFERENCE
2-handed orbital sander								
 		84	0,77	212	10 000	2,5	152 mm - 6"	TOS 15025
		78,9	0,77	212	10 000	5	152 mm - 6"	TOS 15050
Air random orbital sander 2" and 3"								
 		80	0,72	100	16 000		50-75mm 2" - 3"	TPS E16000
Air random orbital sander 2" and 3" in case								
 	Characteristics identical to sander TPS E16000 Supplied in case with : 1- 3" Velcro backing pad 1- 2" Velcro backing pad 10 - 3" abrasive disc 600 grit 10 - 3" abrasive disc 400 grit 10 - 3" abrasive disc 320 grit 10 - 2" abrasive disc 600 grit 10 - 2" abrasive disc 400 grit 10 - 2" abrasive disc 320 grit							
		80	0,72	100	16 000		50-75 mm 2" - 3"	TPS E16000K






AIR SANDER PISTOL AND AIR POLISHER

Efficient	Pressure 6,2 bar	Easy to handle	Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection				
		Noise dB	Weight kg	Consumption l/min	Rotation speed rpm	Diameter plate	Power CV	REFERENCE
3" air sander pistol								
		80	0,7	170	16 000	75 mm - 3"	0,45	TPS 16000
Air random orbital sander 3" in case								
	Case	Characteristics identical to sander TPS 16000 Supplied in case with : 1- 3" Velcro sanding pas (installed) 10 - 3" abrasive disc 60 grit 10 - 3" abrasive disc 80 grit 10 - 3" abrasive disc 120 grit 1 - 3" conditioning pad 1 - 3" stripping disc 1- wrench						
		80		170	16 000	75mm - 3"	0,45	TPS 16000K
Air polisher 3" pistol								
		80	0,77	113	2100	75 mm - 3"	0,3	TPS 2100
Air polisher 3" pistol in case								
	Case	Characteristics identical to sander TPS 2100 Supplied in case with : 1 - Female spindle 1 - 3" Velcro backing pad 1 - 3-1/2" yellow foam compound pad 1 - 3-1/2" white foam compound pad 1 - 3-1/2" wool buffing pad 1 - Key						
		80		113	2100	75 mm - 3"	0,3	TPS 2100K

AIR BELT SANDER

Efficient	Pressure 6,2 bar	Easy to adjust Bluit-in regulator		Thread female R 1/4 (BSPT)	ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2	Supplied with 3 adaptors ISO B, 7.2 - 7.4 mm and ARO for quick connection		
		Consumption l/min	Noise dB	Weight kg	Rotation speed rpm	Power CV	Dimensions belt - mm	REFERENCE
2-handed orbital sander								
 		113	80	0,95	16 000	0,5	10 x 330	TBS 10330
		113	80	1,4	16 000	0,5	20 x 520	TBS 20520



GRINDING

Safety Safety trigger	Pressure 6,2 bar	Easy to handle		ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2	Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection			
		Noise dB(A)	Weight kg	Consumption l/min	Rotation speed rpm	Diameter collet	Power CV	REFERENCE	
Air die grinder									
 		84	0,7	113	22 000	3 & 6 mm	0,5	TDG S22000	
	Composite straight grinder in case								
 		Characteristics identical to grinder TDG S22000. Supplied in case with : 1- 3 mm collet 1- 6 mm collet 10- grinder stones 2- wrenches							
			84		113	22 000	3 & 6 mm	0,5	TDG S22000K


GRINDING

Safety Safety trigger	Pressure 6,2 bar	Easy to handle	ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2			Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection			
Composite straight grinder			Noise dB(A)	Weight kg	Consumption l/min	Rotation speed rpm	Diameter collet	Power CV	REFERENCE	
 			80	1,00	113	4000	3 & 6 mm	0,5	TDG S04000	
Composite straight grinder: 22,000 rpm										
 			80	0,8	113	18 000	3 & 6 mm	0,5	TDG A18000	
Composite straight grinder in case										
 			Characteristics identical to grinder TDG A18000. Supplied in case with : 1- 3 mm collet 1- 6 mm collet 10- grinder stones 2- wrenches							
			80	0,8	113	18 000	3 & 6 mm	0,5	TDG A18000K	
115° Air die grinder										
 			Universal grinder, particularly comfortable in use Composite body, insulating from cold and vibrations Designed for grinding accessories mounted on 6 mm shaft (carbide burr, grinding wheel on shaft rod, other accessories suitable for use at 22,000 rpm) Rear exhaust with ductable silencer Safety trigger to avoid accidental start-up Built-in regulator							
			80	0,8	113	18 000	3 & 6 mm	0,5	TDG B18000	




GRINDING

Safety Safety trigger	Pressure 6,2 bar	Easy to handle	ID supply hose Ø 10 mm for air inlet R 1/4 Ø 13 mm for air inlet R 3/8 Ø 19 mm for air inlet R 1/2			Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection		
			Noise dB(A)	Weight kg	Consumption l/min	Rotation speed rpm	Diameter collet	Power CV	REFERENCE
Air die grinder extended									
			80	1,00	113	22 000	3 & 6 mm	0,5	TDG S22000R
Micro die grinder									
			95	0,3	60	60 000	3 mm	0,5	TDG M60000



DISC CUTTING

Efficient	Pressure 6,2 bar	Thread female R 1/4 (BSPT)	ID supply hose Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2			Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 and ARO for quick connection				
			Rotation speed	Weight kg	Diameter	Consumpt. l/min	Noise dB(A)	Spindle	Thread fem. (BSPT)	REFERENCE
Angle grinder										
			11 000	2	125mm 5"	85	90,4	M 14 x 2.0	R 1/4	TAG 125
			6000	3,3	178mm 7"	113	91,9	M 14 x 2.0	R 3/8	TAG 178



DRILLING

Efficient	Pressure 6,2 bar	Easy to handle	Thread female R 1/4 (BSPT)		ID supply hose Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2	Chuck automatical	Supplied with 3 adaptors Profiles: ISO B, 7.2-7.4 mm and ARO for quick connection	
			Diameter Chuck	Noise dB(A)			Weight	Consumption
Straight air drill								
		10 mm - 3/8"	80	1,04	113	2500	0,5	TAD S382500
		Reversible air drill						
		13 mm - 1/2"	80	1,7	113	W1: 450 W2: 800	0,45	TAD P380800
		10 mm - 3/8"	80	1,15	120	W1: 1000 W2: 2000	0,45	TAD P382000


CHISELLING POWER CHISEL AND STRIPPER

Pressure 6,2 bar	Easy to handle	High performance	ID supply hose Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2		Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection						
			Weight kg	Piston stroke mm	Noise dB	Strike rate cp/min	Consumption l/min	Chuck	Thread fem. (BSPT)	Diameter bore	REFERENCE
Universal power chisel kit											
		Supplied in case with : 5 hex long chisels 175 mm									TAH 0663000K
		1,7	66	115	3000	187	Hex. 10,2 mm	R 1/4			

CHISELLING POWER CHISEL AND STRIPPER

Pressure 6,2 bar	Easy to handle	High performance	ID supply hose Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2				Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection			
		Weight kg	Piston stroke mm	Noise dB	Strike rate cp/min	Consumpt. l/min	Chuck	Thread fem. (BSPT)	Diameter bore	REFERENCE
Heavy duty air hammer with vibration damped										
	NEW	2,00	70	111	3000	220	Hex. 10,2 mm	R 1/4	19 mm	TAH 0703000VD
		2,2	95	110	2100	232	Hex. 10,2 mm	R 1/4	19 mm	TAH 0952100VD
Power chisel										
	NEW	9,5	115	113	1900	158	14,75 mm	R 3/8	28,5 mm	TAH 1151900


CHISELLING POWER CHISEL AND STRIPPER

Pressure 6,2 bar	Easy to handle	Thread female R 1/4	ID supply hose Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2				Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection			
		Noise dB	Weight kg	Consumption l/min	Piston stroke mm	Strike rate cp/min	Diameter bore	REFERENCE		
19-needle power stripper										
	NEW	19 needles, Ø 3mm, Length 180mm								
		109	2,7	85	33	3700	23,5 mm	TSP 0333700		

CUTTING AIR TOOLS

Efficient	Pressure 6,2 bar	Thread female R 1/4 (BSPT)	ID supply tool Ø 10mm for air inlet R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2			Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4mm and ARO for quick connection				
		Noise dB	Consumpt. l/min	Strike rate cp/min	Power CV	Weight kg	Rotation speed tr/min	Diameter Disk dia.	Strike rate cpm	REFERENCE
Air body saw										
	<p>NEW</p> <p>Blade travel : 10 mm Width of cut : Steel : 2 mm Alu : 3 mm</p>	80	114	5000						TCS 05000
Air metal shear pistol										
	<p>NEW</p> <p>Thickness of cut : Steel: 1,2 mm Alu : 1,4 mm Width of cut : 5,5 mm</p>	92	113	2500	0,45	1,3				TCS 02500
Air cut-off tool										
	<p>NEW</p> <p>Tool designed for stripping and grinding accessories on 6 mm shafts (brush, flutter wheel, textured disk) Housing with sleeve for ergonomic grip Rear exhaust with ductable silencer Safety trigger to avoid accidental start-up Built-in regulator</p>	87	113		0,5	0,84	20 000	7,5mm 3"		TCS 20000
Air nibbler										
	<p>NEW</p> <p>Ø cutter : 4 mm Width of cut : Steel : 1,4 mm Alu : 1,6 mm</p>	87	57			0,805			3500	TCS 03500

HYDRAULIC AIR RIVETER

Efficient	Pressure 6,2 bar	Thread female R 1/4 (BSPT)	ID supply tool Ø 10mm for air inlet R R 1/4 Ø 13mm for air inlet R 3/8 Ø 19mm for air inlet R 1/2	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection				
		Noise dB	Consumption l/min	Dimensions rivets mm	Piston stroke mm	Weight kg	Traction force kg	REFERENCE
Hydraulic air riveter with vacuum system								
	Pop riveting gun							
	60	123	2,4 - 4,8	14	1,5	1219	TAR 481220	
	63	148	2,4 6,4	19	2,14	1894	TAR 641895	

SPECIAL TOOLS

Efficient	Pressure 6,2 bar	Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection					
		DESCRIPTION						REFERENCE
Hydraulic punch & flange tool 3/16"								
	Max sheet metal thickness : 1,6 mm Punch Ø : 5 mm Power: 0,5 cv - 370 W Air consumption: 113 l/min Noise: 88 dBA Weight: 1,45 Kg						TPF 5	
Air caulking gun								
	Tube dimensions: 50 x 236 mm Air consumption : 120 l/min Capacity : 310 - 400 ml Noise : 91 db(A) Weight: 1,2kg						TCG CB400	
Grease gun								
	Air consumption : 120 l/min Capacity : 400 cc - 14 oz Weight : 1 kg						TCG GR400	

SPECIAL TOOLS

Efficient	Pressure 6,2 bar	Thread female R 1/4 (BSPT)	Supplied with 3 adaptors Profiles: ISO B, 7.2 - 7.4 mm and ARO for quick connection
DESCRIPTION			REFERENCE
Air stripping tool with eraser pad			
 <p>NEW</p>		<p>Ø axe thread : 5/16" Consumption : 113 l/min Rotation speed : 4000 tr/min Power : 0,5 CV - 370W Noise : 80 dB(A) Ø pad: 3" - 75 mm</p>	TDG P04000
Air metal blaster			
 <p>NEW</p>		<p>Power: 0.5 CV - 370 W Rotation speed: 3500 tr/min Air consumption: 110 l/min</p>	TMB 3500
Air metal blaster in case			
 <p>NEW</p>	<p>Case</p>	<p>Characteristics identical to blaster TMB 3500 Supplied in case with :</p> <ul style="list-style-type: none"> 1 – Hub 3 – Eraser rubber wheel 3 – Clean and stripper 3 – 23 mm stripping brush 1 – Swivel connector <p>Power : 0,5 cv Rotation speed : 3 500 tr/min Air consumption : 110 l/min</p>	TMB 3500K
Air windshield remove knife			
 <p>NEW</p>		<p>Air consumption : 113 l/min Power : 0,5 cv - 370 W Blows per minute : 20 000 cpm Noise : 87 dB(A)</p>	TWK 20000
Air engraving stylus			
 <p>NEW</p>		<p>Power : 0,5 cv - 370 W Air consumption : 40 l/min Rotation speed : 13 000 rpm Noise : 75 dBA Weight : 0,24 kg</p>	TES 34000







Head office: PREVOST SAS
Parc d'activités des Glaisins - C.S. 90208
74942 ANNECY-LE-VIEUX CEDEX - FRANCE
Tél. +33 (0)4 50 64 04 45 - Fax +33 (0)4 50 64 00 10
E-mail: sales@prevost.eu - www.prevost.eu

PREVOST UK
The Pavilions - Bridgefold road
Rochdale OL11 5BX - United Kingdom
Tel. (+44) 0844 800 2788 - Fax (+44) 0844 800 2789
E-mail: sales@prevost-ltd.co.uk - www.prevost.eu



AT CAT14E- 10/14

This document is non-contractual.
PREVOST reserves the right to modify
the features of its range without prior notice.
Publication Prevost - 10-2014